



M8S-500S POWER AMPLIFIER

The M8s-500s is a Power Amplifier fit of the highest levels of reproduction.

The M8s-500s has received outstanding reviews and an enthusiastic reception from knowledgeable audiophiles. The combination of high power and cutting edge technical performance has proved a compelling combination.

However, some customers do not have the space for two large monoblocs and do not necessarily need that much power. For them we have designed the M8s-500s. Pairing it with the matching M8 Preamp gives an amplification system fit of the highest levels of reproduction.

With the update to the S-version, some, already high quality components have been upgraded to even higher quality ones. Thus the models of the updated S-version have a more open sound while preserving at the same time the musicality of their predecessors.

MUSICAL FIDELITY

The M8s-500s is a fully balanced stereo amplifier which delivers 500wpc, which almost doubles into 4ohms. The M8s-500s is engineered for very low distortion typically less than .001% of 1kz and below .005% at 20kHz. Even at the ridiculous level of 50kHz distortion is a mere 0.02% creeping up to around 0.06% at the even more unreasonable figure of 100kHz. These may be measurements of frequencies never encountered in the real world but they prove a point; that the M8s-500s significant less distortion than rival designs.

Like the M8-700m the M8s-500s has very low noise. Its combination of huge power reserves, low distortion and low noise contribute to its effortless performance. It delivers everything from delicate detail to massive dynamic slam with incredible speed and precision.

Whatever style of music you listen to the M8s-500s serves it up in a spacious sound stage with outstanding realism.

Its power and balance mean that the M8s-500s can drive just about any loudspeaker you choose. It is, of course, the perfect partner/visually and sonically for our M8 preamp.





M8S-500S POWER AMPLIFIER

SPECIFICATION

Power Amplifier:

- Power output: 500 Watts per channel into 8 Ohms (27 dBW)
- THD(+ noise): <0.007% typical
- Signal to Noise Ratio: >120dB ,A¹ weighted
- Frequency Response: +0, -1dB, 10Hz to 80kHz

Inputs

- 1x RCA - Line Level
- 1x XLR Balanced - Line Level
- 1x Trigger input 3.5mm (1/8") mono jack

Outputs

- 2x Loudspeaker outputs
- 1x XLR - Line Level (loop out)
- 1x RCA- Line Level (loop out)
- 1x Trigger output 3.5mm (1/8") mono jack

General

- Dimensions - WxHxD (mm): 440 x 160 x 460
- Weight (unpacked / packed): 29 kg / 34.5 kg