



Power Box RS2 Sources

Universal linear power supply for 4 RS/RS2 devices

Colour options:  

- Powers four 20V RS/RS2 devices
- One power supply for all source components
- Improved sound stage and detail resolution
- Cleanest power using non-switching power supply
- Soft start system avoids current inrush
- Audio type toroidal transformer
- Main isolating transformer with copper foil shielding
- Secondary voltage rectification with precise regulation
- High filtration capacity (10.000 μ F)
- Low ESR capacitors
- Low noise components with surge protection
- Rigid aluminium casing protects against interference
- Available in silver or black
- Made in Europe

Input voltage: 115V/230V AC

Output voltage/current: 4 x 20V \pm 0,5% / 2A

Ripple: max. 6mV pp

Filtration capacity: 10.000 μ F

incl. accessories: 4x mini XLR/mini XLR connection cables

Dimensions W x H x D: 206 x 71 x 209 mm

Weight: 3550 g

Cleanest power for ultimate sound!

The power supply is a very important part of the audio path and significantly contributes to the sonic quality of an audio product.

With the new Power Box RS2 Sources you can connect up to four 20V RS/RS2 devices and benefit from the perfect power contribution. Four standard mini XLR to mini XLR connection cables are included in the packaging.

A linear power supply consists of a massive toroidal transformer, which avoids penetration of interferences from mains into the audio component. The built-in transformer has a much higher power reserve compared to the standard power adapter. It has very low output impedance and in combination with large filtration capability it can easily manage all power needs. Sound staging, darkness of silent backgrounds and small detail resolution will improve strongly and contribute to a far better overall performance of each component.

Power Box RS2 Sources is made in Europe and available in a black or silver full aluminium housing.

